




# SEQUE DESIGNS

Item	Description
1	Base Plate
2/2a	36" Half Round Vertical extrusion
3	36.25" Half Round Vertical extrusion
3a	36" Half Round Vertical extrusion
4	Curved Horizontal Extrusion
5	Curved Horizontal Extrusion
6	36.25" Half Round Vertical extrusion
6a	36" Half Round Vertical extrusion
7/7a	36" Half Round Vertical extrusion
8	Curved Horizontal Extrusion
9	Curved Horizontal Extrusion

- Steps:
- 1) Attach lower verticals [3 and 6] together as shown. Note: Attach lower V10. Slide H extrusion between grooves. Then attach upper V10.
  - 2) Attach upper verticals [3a and 6a] together as shown. Note: Attach lower V10. Slide H extrusion between grooves. Then attach upper V10.
  - 3) Connect upper verticals [2a, 3a, 6a, and 7a] to lower verticals [2, 3, 6, and 7].\*
  - 4) Connect vertical assemblies [2/2a and 7/7a] to base plates [1].
  - 5) Connect horizontals [4, 5, 8 and 9] between vertical extrusions as shown.
- Note: The SEG extrusion should be in the groove of the extrusion, if not then slide into place as shown below in detail.*
- 6) Place lights staggered inside the vertical extrusions making sure to run cords down thru bottom.
  - 7) Attach Sintra Caps to Top and Bottom of assembled lightbox.



WHEN DISASSEMBLING ALUMINUM EXTRUSION, TIGHTEN ALL SETSCREWS AND LOCKS TO PREVENT LOSS DURING SHIPPING



Using Your Setup Instructions

The Visionary Designs Setup Instructions are created specifically for your configuration. They are laid out sequentially, including an exploded view of the entire display, and then a logical series of detailed steps to assemble the main structure and components. We encourage you to study the instructions **before** attempting to assemble your exhibit.

Each page reminds you to tighten the setscrews after disassembling your exhibit to prevent loss of the locks and setscrews (see below in RED). This is VERY IMPORTANT.

Cleaning and Packing Your Display

- 1) Use care when cleaning aluminum extrusion or acrylic inserts. Use only non-abrasive cleaners.
- 2) When cleaning laminate inserts or countertops, use mild cleansers and a soft material such as cotton.
- 3) Keep all display components away from extreme heat and long exposure to sunlight to avoid warping and fading.
- 4) Retain all packing material. It will make re-packing much easier and will reduce the likelihood of shipping damage.




**The Tool**  
Most Visionary Designs exhibits can be assembled with the supplied Hex Key Tool. Occasionally, a flat head screwdriver may be required.



**Typical Connection**  
Most horizontal extrusion connections have a patented expandable lock. This lock inserts into the groove of an opposing extrusion. Tightening the lock with the Hex Key Tool expands the lock and creates a strong positive connection.




**Typical Connection (cont'd)**




**Numbered Label**  
Each extrusion contains a numbered label which corresponds with setup instructions. The label is located within a groove of the extrusion (when possible). With Visionary Designs the labels contain Black numbers unless otherwise specified.



**Horizontal Inline Connection** (remove only one setscrew)  
Remove only (1) setscrew when disassembling. Replace setscrew in extrusion after assembling it. Before packing, replace setscrew in extrusion to avoid losing it.




**Base Plate Connection**  
Attach base plate to round or square vertical extrusion using the bolt provided. Be careful not to strip the threads.



**Vertical Connection** (remove only two setscrews)  
When vertical extrusions are packed in portable cases rather than crates or tubs, they must be broken down into smaller sections which then require assembly.  
  
Remove only (2) setscrews when disassembling. Replace setscrews in extrusion after assembling it. Before packing, replace setscrews in extrusion to avoid losing them.

# SEG Graphic: To Ensure Proper Fit




It is important to first insert graphic into each alternater corner then to the sides of the frame.  
If this is not done, graphic will not fit into the frame correctly.



**Step 1**  
Insert corner A.  
Turn edge of graphic so silicon welt is perpendicular to face of graphic.  
Insert narrow side of welt with fabric to outside into the channel.  
Repeat for other side of this corner.




**Step 2**  
Repeat Step 1 for opposite corner C, then insert corner B, followed by corner corner D, to complete the installation of the corners.




**Step 3**  
Once all corners are inserted, press one silicon edge into channel from corners and work toward the center.  
Make sure welt is fully inserted into channel. Continue until all sides are done. Smooth out edges of graphic.

## Graphic Removal




To remove the graphic from the frame, locate the fabric pull tab.  
Gently pull up on the tab to remove the fabric.

Top View of Each Level



WHEN DISASSEMBLING ALUMINUM EXTRUSION, TIGHTEN ALL  
SETSCREWS AND LOCKS TO PREVENT LOSS DURING SHIPPING

Top View of Each Level



WHEN DISASSEMBLING ALUMINUM EXTRUSION, TIGHTEN ALL SETSCREWS AND LOCKS TO PREVENT LOSS DURING SHIPPING